

# DECLARATION OF PERFORMANCE

DoP number: 17106C057W4110

Product name:

Porotherm 25 N+F

Identification code of product-type is DoP-number



# Wienerberger


Винербергер ЕООД  
ул. Св. Пимен Зографски - 1172 София  
България

Intended use in masonry walls, columns and partitions for:  
Assessment and verification of constancy of performance:  
Harmonised standard:  
Notified body/ies:

protected masonry  
System 2+  
EN 771-1:2011+A1:2015  
1871

## Declared performance/s of a P - masonry unit

Dimensions and tolerances		T1	R1
Length:	mm	375 ± 8	12
Width:	mm	250 ± 6	9
Height:	mm	238 ± 6	9
Tolerance:	category	T1	
Range:	category	R1	
Flatness of bed faces:	mm	NPD	
Plane parallelism:	mm	NPD	
Configuration			
Group of the unit:	-	2	
Volume of all formed voids:	%	NPD	
Volume of frogs:	%	NPD	
Density			
Gross dry density:	kg/m <sup>3</sup>	750	
Net dry density:	kg/m <sup>3</sup>	NPD	
Tolerance:	category / %	D1 / 10	
Compressive strength for Category I product			
Perpendicular to bedface:	N/mm <sup>2</sup>	10	
Perpendicular to header:	N/mm <sup>2</sup>	NPD	
Perpendicular to header 2:	N/mm <sup>2</sup>	0	
Bond strength:	N/mm <sup>2</sup>	0,15	
Thermal conductivity λ10,dry,unit:	W/(m·K)	0.26	
Water vapour permeability:	-	μ = 5/10	
Durability:	category	F0	
Water absorption:	%	NPD	
Initial rate of water absorption:	kg/(m <sup>2</sup> ·min)	NPD	
Active soluble salt content:	category	S0	
Moisture movement:	mm/m	NPD	
Reaction to fire:	class	A1	
Dangerous substances:	-	NPD	



actual configuration may vary slightly

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

2017-04-18

CEO

Атанас Буглов

Винербергер ЕООД  
ул. Св. Пимен Зографски - 1172 София  
България